

ICON FUV Science Level 1 Data

This document describes the data product for ICON FUV Level 1 FUV-B Altitude Profile File, which is in NetCDF4 format.

The ICON Far UltraViolet (FUV) imager contributes to the ICON science objectives by providing remote sensing measurements of the daytime and nighttime atmosphere/ ionosphere. During sunlit atmospheric conditions, ICON FUV images the limb altitude profile in the shortwave (SW) band at 135.6 nm and the longwave (LW) band at 157 nm perpendicular to the satellite motion to retrieve the atmospheric O/N₂ ratio. In conditions of atmospheric darkness, ICON FUV measures the 135.6 nm recombination emission of O+ ions used to compute the nighttime ionospheric altitude distribution.

The ICON Far Ultra-Violet (FUV) imager is a Czerny–Turner design Spectrographic Imager with two exit slits and corresponding back imager cameras that produce two independent images in separate wavelength bands on two detectors. For this science product, the 18x24 degree FOV is divided and co-added to produce 6 high sensitivity profiles with each nominally 12 second integration. These inform daytime and nighttime retrievals of the ionospheric composition and density (See Stephan et al and Kamalabadi et al, noted in the acknowledgements section of this file). Pointing and geolocation information are available in the FUV ancillary data also available at <https://icon.ssl.berkeley.edu>

More details about the mission, data products, responsibility, and data use can be found at the end of this document.

Each FUVB Level-1 file contains global attributes explaining the major properties of the file and variables. This is an example from one file.

0 ACKNOWLEDGEMENT This is a data product from the NASA Ionospheric Connection Explorer mission, an Explorer launched at 21:59:45 EDT on October 10, 2019, from Cape Canaveral AFB in the USA. Guidelines for the use of this product are described in the ICON Rules of the Road (<http://icon.ssl.berkeley.edu/Data>).

1 ADID_REF NASA Contract > NNG12F45C

2 CALIBRATION_FILE See calibration files in general attribute fields FLATFIELD_CORRECTION, BACKGROUND_CORRECTION, RAYLEIGH_CONVERSION

3 CONVENTIONS SPDF ISTP/IACF Modified for NetCDF (v0.8)

4 DATA_LEVEL L1

5 DATA_TYPE APIDxE3 > ICON Application ID 0xE3: FUV Science Level 0.5 Data > FUV Science Level 1 Data

6 DATA_REVISION 0

7 DATA_VERSION 2.00000

8 DATA_VERSION_MAJOR 2

9 DATE_END 2020-02-04T23:59:53 UTC

10 DATE_START 2020-02-04T00:00:00 UTC

11 DATE_STOP 2020-02-04T23:59:53 UTC

12 DESCRIPTION ICON FUV Level 1 FUV-B Altitude Profile File

13 DESCRIPTOR FUV-B > ICON FUV-B L1 Science Altitude Profile File

14 DISCIPLINE Space Physics > Ionospheric Science

15 FILE ICON_L1_FUV_LWP_20200204_v02r000.NC

16 FILE_DATE Fri Aug 14 08:31:44 2020

17 GENERATED_BY ICON SDC > ICON FUV L1 Processor v1, Tori Fae (tfae@paradigm.ssl.berkeley.edu) and Harald Frey (hfrey@ssl.berkeley.edu)

18 GENERATION_DATE 20200814

19 HISTORY Version 2 Created by ICON FUV L1 processing with icn_fuv_create_lwp_structure.pro Fri Sep 18 12:06:56 2020

MODIFICATION HISTORY:

Written by: Harald Frey, Date: January 27, 2017

2019-12-11 major updates for calibration conversion

2020-01-22 made stripes consistent with LW, P6 looking forward, background, error

2020-03-20 new backgrounds, flatfields, quality parameter etc.

2020-04-06 allow negative values, bkg variable in Rayleighs etc.
2020-05-28 new background, uncertainty, stars removed
2020-08-17 no negative values sublimb, new attributes, turrets, mark insufficient HV
2020-09-14 correctly deal with forced turret for sun protection
20 HTTP_LINK <http://icon.ssl.berkeley.edu>
21 INSTRUMENT FUV-B
22 INSTRUMENT_TYPE Imagers (Space)
23 LINK_TEXT All ICON information and data can be found at the ICON web page icon.ssl.berkeley.edu
24 LINK_TITLE ICON Website
25 LOGICAL_FILE_ID ICON_L1_FUV_LWP_20200204_v02r000
26 LOGICAL_SOURCE ICON_L0P_FUV-B_Science-TDI1_2020-02-04
27 LOGICAL_SOURCE_DESCRIPTION ICON FUV-B Level 1 Science Altitude Profile File
28 MISSION_GROUP Ionospheric Investigations
29 MODS See history
30 PARENTS Names of all L0 Files
31 PI_AFFILIATION UC Berkeley > SSL
32 PI_NAME T. J. Immel
33 PROJECT NASA > ICON
34 RULES_OF_USE Public Data for Scientific Use
35 SOFTWARE_VERSION ICON SDC > ICON FUV L1 Processor v1.0
36 SOURCE_NAME ICON > Ionospheric Connection Explorer
37 SPACECRAFT_ID NASA > ICON - 493
38 TEXT ICON explores the boundary between Earth and space - the ionosphere - to understand the physical connection between our world and the immediate space environment around us. Visit '<http://icon.ssl.berkeley.edu>' for more details.
39 TIME_RESOLUTION 12000 milliseconds
40 TITLE ICON FUV Level 1 FUV-B Altitude Profile File
41 EPOCH0 1970-01-01/00:00:00
42 FILE_NAMING_CONVENTION source_datatype_descriptor
43 PROCESS_LEVEL L1
44 SAMPLE_TIME 12
45 SAMPLE_UNIT Seconds
46 SATELLITE_ID ICON
47 TEXT_SUPPLEMENT Explanation of global attributes
48 FLATFIELD_CORRECTION Values of flatfield correction for each stripe
49 BACKGROUND_CORRECTION saa_files_2020-035
50 RAYLEIGH_CONVERSION Values for Rayleigh conversion

Use of this product for analysis depends on the combined use of the ancillary FUV data product which contains geopositioning data and instrument pointing details.

History

Version 3 Created by ICON FUV L1 processing with icn_fuv_create_lwp_structure.pro Tue Sep 22 08:13:56 2020

MODIFICATION HISTORY:

Written by: Harald Frey, Date: January 27, 2017

2019-12-11 major updates for calibration conversion

2020-01-22 made stripes consistent with LW, P6 looking forward, background, error

2020-03-20 new backgrounds, flatfields, quality parameter etc.

2020-04-06 allow negative values, bkg variable in Rayleighs etc.

2020-05-28 new background, uncertainty, stars removed

2020-08-17 no negative values sublimb, new attributes, turrets, mark insufficient HV

2020-09-14 correctly deal with forced turret for sun protection

Dimensions

NetCDF files contain **variables** and the **dimensions** over which those variables are defined. First, the dimensions are defined, then all variables in the file are described.

The dimensions used by the variables in this file are given below, along with nominal sizes. Note that the size may vary from file to file. For example, the "Epoch" dimension, which describes the number of time samples contained in this file, will have a varying size.

Dimension Name	Nominal Size
Epoch	4301
Rows	256
Columns	1
Stripes	6

Variables

Variables in this file are listed below. First, "data" variables are described, followed by the "support_data" variables, and finally the "metadata" variables. The variables classified as "ignore_data" are not shown.

data

Variable Name	Description	Units	Dimensions
ICON_L1_FUVB_LWP_Raw_M9	FUVB LW channel raw CCD counts profile for -9 to -6 degrees FOV Vertical raw CCD counts profile for -9 to -6 degrees FOV	counts	Epoch, Rows
ICON_L1_FUVB_LWP_Raw_M6	FUVB LW channel raw CCD counts profile for -6 to -3 degrees FOV Vertical raw CCD counts profile for -6 to -3 degrees FOV	counts	Epoch, Rows
ICON_L1_FUVB_LWP_Raw_M3	FUVB LW channel raw CCD counts profile for -3 to 0 degrees FOV Vertical raw CCD counts profile for -3 to 0 degrees FOV	counts	Epoch, Rows
ICON_L1_FUVB_LWP_Raw_P0	FUVB LW channel raw CCD counts profile for 0 to +3 degrees FOV Vertical raw CCD counts profile for 0 to +3 degrees FOV	counts	Epoch, Rows
ICON_L1_FUVB_LWP_Raw_P3	FUVB LW channel raw CCD counts profile for +3 to +6 degrees FOV Vertical raw CCD counts profile for +3 to +6 degrees FOV	counts	Epoch, Rows
ICON_L1_FUVB_LWP_Raw_P6	FUVB LW channel raw CCD counts profile for +6 to +9 degrees FOV Vertical raw CCD counts profile for +6 to +9 degrees FOV	counts	Epoch, Rows
ICON_L1_FUVB_LWP_PROFILE_M9	FUVB LW channel altitude column brightness for -9 to -6 degrees FOV Vertical profile for -9 to -6 degrees FOV	Rayleigh	Epoch, Rows
ICON_L1_FUVB_LWP_PROFILE_M6	FUVB LW channel altitude column brightness for -6 to -3 degrees FOV Vertical profile for -6 to -3 degrees FOV	Rayleigh	Epoch, Rows
ICON_L1_FUVB_LWP_PROFILE_M3	FUVB LW channel altitude column brightness for -3 to 0 degrees FOV Vertical profile for -3 to 0 degrees FOV	Rayleigh	Epoch, Rows
ICON_L1_FUVB_LWP_PROFILE_P0	FUVB LW channel altitude column brightness for 0 to +3 degrees FOV Vertical profile for 0 to +3 degrees FOV	Rayleigh	Epoch, Rows

Variable Name	Description	Units	Dimensions
ICON_L1_FUVB_LWP_PR_OF_P3	FUVB LW channel altitude column brightness for +3 to +6 degrees FOV Vertical profile for +3 to +6 degrees FOV	Rayleigh h	Epoch, Rows
ICON_L1_FUVB_LWP_PR_OF_P6	FUVB LW channel altitude column brightness for +6 to +9 degrees FOV Vertical profile for +6 to +9 degrees FOV	Rayleigh h	Epoch, Rows
ICON_L1_FUVB_LWP_PR_OF_M9_Error	FUVB LW channel altitude column brightness for -9 to -6 degrees FOV error Vertical profile for -9 to -6 degrees FOV error using uncertainty_calculator_v2r0. Statistical 1-sigma error values associated with the brightness profiles. After estimating the instrument gain and the background signal statistics from the 24 hours of brightness profiles, 1-sigma errors are calculated for each altitude profile as a function of these quantities and the measured signal level.	Rayleigh h	Epoch, Rows
ICON_L1_FUVB_LWP_PR_OF_M6_Error	FUVB LW channel altitude column brightness for -6 to -3 degrees FOV error Vertical profile for -6 to -3 degrees FOV error using uncertainty_calculator_v2r0. Statistical 1-sigma error values associated with the brightness profiles. After estimating the instrument gain and the background signal statistics from the 24 hours of brightness profiles, 1-sigma errors are calculated for each altitude profile as a function of these quantities and the measured signal level.	Rayleigh h	Epoch, Rows
ICON_L1_FUVB_LWP_PR_OF_M3_Error	FUVB LW channel altitude column brightness for -3 to 0 degrees FOV error Vertical profile for -3 to 0 degrees FOV error using uncertainty_calculator_v2r0. Statistical 1-sigma error values associated with the brightness profiles. After estimating the instrument gain and the background signal statistics from the 24 hours of brightness profiles, 1-sigma errors are calculated for each altitude profile as a function of these quantities and the measured signal level.	Rayleigh h	Epoch, Rows
ICON_L1_FUVB_LWP_PR_OF_P0_Error	FUVB LW channel altitude column brightness for 0 to +3 degrees FOV error Vertical profile for 0 to +3 degrees FOV error using uncertainty_calculator_v2r0. Statistical 1-sigma error values associated with the brightness profiles. After estimating the instrument gain and the background signal statistics from the 24 hours of brightness profiles, 1-sigma errors are calculated for each altitude profile as a function of these quantities and the measured signal level.	Rayleigh h	Epoch, Rows

Variable Name	Description	Units	Dimensions
ICON_L1_FUVB_LWP_PR_OF_P3_Error	FUVB LW channel altitude column brightness for +3 to +6 degrees FOV error Vertical profile for +3 to +6 degrees FOV error using uncertainty_calculator_v2r0. Statistical 1-sigma error values associated with the brightness profiles. After estimating the instrument gain and the background signal statistics from the 24 hours of brightness profiles, 1-sigma errors are calculated for each altitude profile as a function of these quantities and the measured signal level.	Rayleigh h	Epoch, Rows
ICON_L1_FUVB_LWP_PR_OF_P6_Error	FUVB LW channel altitude column brightness for +6 to +9 degrees FOV error Vertical profile for +6 to +9 degrees FOV error using uncertainty_calculator_v2r0. Statistical 1-sigma error values associated with the brightness profiles. After estimating the instrument gain and the background signal statistics from the 24 hours of brightness profiles, 1-sigma errors are calculated for each altitude profile as a function of these quantities and the measured signal level.	Rayleigh h	Epoch, Rows
ICON_L1_FUVB_LWP_PR_OF_M9_BKG	FUVB LW channel altitude column brightness for -9 to -6 degrees FOV background Vertical profile for -9 to -6 degrees FOV bkg	Rayleigh h	Epoch, Rows
ICON_L1_FUVB_LWP_PR_OF_M6_BKG	FUVB LW channel altitude column brightness for -6 to -3 degrees FOV background Vertical profile for -6 to -3 degrees FOV bkg	Rayleigh h	Epoch, Rows
ICON_L1_FUVB_LWP_PR_OF_M3_BKG	FUVB LW channel altitude column brightness for -3 to 0 degrees FOV background Vertical profile for -3 to 0 degrees FOV bkg	Rayleigh h	Epoch, Rows
ICON_L1_FUVB_LWP_PR_OF_P0_BKG	FUVB LW channel altitude column brightness for 0 to +3 degrees FOV background Vertical profile for 0 to +3 degrees FOV bkg	Rayleigh h	Epoch, Rows
ICON_L1_FUVB_LWP_PR_OF_P3_BKG	FUVB LW channel altitude column brightness for +3 to +6 degrees FOV background Vertical profile for +3 to +6 degrees FOV bkg	Rayleigh h	Epoch, Rows
ICON_L1_FUVB_LWP_PR_OF_P6_BKG	FUVB LW channel altitude column brightness for +6 to +9 degrees FOV background Vertical profile for +6 to +9 degrees FOV bkg	Rayleigh h	Epoch, Rows
ICON_L1_FUVB_LWP_PR_OF_M9_CLEAN	FUVB LW channel altitude column brightness for -9 to -6 degrees FOV without stars Vertical profile for -9 to -6 degrees FOV without stars using artifact_removal_v1r4	Rayleigh h	Epoch, Rows

Variable Name	Description	Units	Dimensions
ICON_L1_FUVB_LWP_PR_OF_M6_CLEAN	FUVB LW channel altitude column brightness for -6 to -3 degrees FOV without stars Vertical profile for -6 to -3 degrees FOV without stars using artifact_removal_v1r4	Rayleigh h	Epoch, Rows
ICON_L1_FUVB_LWP_PR_OF_M3_CLEAN	FUVB LW channel altitude column brightness for -3 to 0 degrees FOV without stars Vertical profile for -3 to 0 degrees FOV without stars using artifact_removal_v1r4	Rayleigh h	Epoch, Rows
ICON_L1_FUVB_LWP_PR_OF_P0_CLEAN	FUVB LW channel altitude column brightness for 0 to +3 degrees FOV without stars Vertical profile for 0 to +3 degrees FOV without stars using artifact_removal_v1r4	Rayleigh h	Epoch, Rows
ICON_L1_FUVB_LWP_PR_OF_P3_CLEAN	FUVB LW channel altitude column brightness for +3 to +6 degrees FOV without stars Vertical profile for +3 to +6 degrees FOV without stars using artifact_removal_v1r4	Rayleigh h	Epoch, Rows
ICON_L1_FUVB_LWP_PR_OF_P6_CLEAN	FUVB LW channel altitude column brightness for +6 to +9 degrees FOV without stars Vertical profile for +6 to +9 degrees FOV without stars using artifact_removal_v1r4	Rayleigh h	Epoch, Rows

support_data

Variable Name	Description	Units	Dimensions
Epoch	Epoch Center time of the exposure, milliseconds after 1970-01-01/00:00:00 UT	milliseconds	Epoch
ICON_L1_FUVB_LWP_Start_Times	Start time Start time of the exposure, UT		Epoch
ICON_L1_FUVB_LWP_Stop_Times	Stop time Stop time of the exposure, UT		Epoch
ICON_L1_FUVB_LWP_Center_Times	Center time Center time of the exposure, UT		Epoch
ICON_L1_FUVB_LWP_Integration_Time	Time Integration time for integration in seconds	seconds	Epoch

Variable Name	Description	Units	Dimensions
ICON_L1_FUVB_LWP_Chain_ID	Number Chain ID for integration in seconds	number	Epoch
ICON_L1_FUVB_LWP_Quality_Flag	Quality indicator (also quickly shows times when images are available) QUALITY_FLAG is an indicator of data quality = 0 = No errors or quality conditions, LVLH 1 = No errors or quality conditions, R-LVLH 2 = Lunar calibration 3 = Insufficient high voltage 4 = Nadir calibration 5 = Zero wind calibration 6 = Bad pointing 7 = S/C attitude slew 8 = Conjugate observation 9 = Stellar calibration 10 = Unreliable background subtracted 17 = unspecified error condition	number	Epoch
ICON_L1_FUV_Mode	Data collection mode Data collection mode of FUV instrument 1 = Dayside science 2 = Nightside science 3 = Calibration 4 = Nadir 5 = Conjugate 6 = Stars 7 = Ram 8 = Off Target 9 = Engineering 13 = Unknown	number	Epoch
ICON_L1_FUVB_LWP_HV_PHOS	HV of LW channel phosphor HV of phosphor screen	Volt	Epoch
ICON_L1_FUVB_LWP_HV_MCP	HV of LW channel MCP HV of MCP	Volt	Epoch
ICON_L1_FUV_Turret	FUV turret angle FUV turret angle in degrees with respect to nominal center position	degree	Epoch
ICON_L1_FUVB_CCD_TEMP	FUVB CCD temperature FUVB CCD temperature	degree C	Epoch
ICON_L1_FUVB_Board_TEMP	FUVB board temperature FUVB digital board temperature	degree C	Epoch
ICON_L1_FUVB_HV_TEMP	FUVB HVPS temperature FUVB HVPS temperature	degree C	Epoch

Variable Name	Description	Units	Dimensions
ICON_L1_FUV_IMG_TEM_P	FUV imager enclosure temperature FUV imager enclosure temperature	degree C	Epoch
ICON_L1_FUV_OPT_TEM_P	FUV optics bench temperature FUV optics bench temperature	degree C	Epoch
ICON_L1_FUV_Turret_TEMP	FUV turret temperature FUV turret temperature	degree C	Epoch
ICON_L1_FUV_Scan_TE_MP	FUV scan mirror temperature FUV scan mirror temperature	degree C	Epoch
ICON_L1_FUVB_LWP_GAIN_DAY	Average value of CCD output electrons per primary photo-electron in the image tube during day. It is calculated using the statistics of 24 hours of day profiles. Gain of each stripe is calculated independently. Gain for profiles	CCD electrons / photo-electron	Stripes

metadata

Variable Name	Description	Units	Dimensions
Rows	Row Number Vertical row numbers for profiles	number	Rows
ICON_L1_FUVB_Azimuth	Azimuth of FUVB channel with respect to spacecraft coordinates FUVB channel pointing azimuth	degree	Epoch
ICON_L1_FUVB_Elevation	Elevation of FUVB channel with respect to spacecraft coordinates FUVB channel pointing elevation	degree	Epoch
ICON_L1_FUVB_Roll	Roll of FUVB channel with respect to spacecraft coordinates FUVB channel pointing roll	degree	Epoch

Acknowledgement

This is a data product from the NASA Ionospheric Connection Explorer mission, an Explorer launched at 21:59:45 EDT on October 10, 2019, from Cape Canaveral AFB in the USA. Guidelines for the use of this product are described in the ICON Rules of the Road (<http://icon.ssl.berkeley.edu/Data>).

Responsibility for the mission science falls to the Principal Investigator, Dr. Thomas Immel at UC Berkeley:
Immel, T.J., England, S.L., Mende, S.B. et al. Space Sci Rev (2018) 214: 13. <https://doi.org/10.1007/s11214-017-0449-2>

Responsibility for the validation of the L1 data products falls to the instrument lead investigators/scientists.

- * EUV: Dr. Eric Korpela : <https://doi.org/10.1007/s11214-017-0384-2>
- * FUV: Dr. Harald Frey : <https://doi.org/10.1007/s11214-017-0386-0>
- * MIGHTI: Dr. Christoph Englert : <https://doi.org/10.1007/s11214-017-0358-4>, and
<https://doi.org/10.1007/s11214-017-0374-4>
- * IVM: Dr. Roderick Heelis : <https://doi.org/10.1007/s11214-017-0383-3>

Responsibility for the validation of the L2 data products falls to those scientists responsible for those products.

- * Daytime O and N2 profiles: Dr. Andrew Stephan : <https://doi.org/10.1007/s11214-018-0477-6>
- * Daytime (EUV) O+ profiles: Dr. Andrew Stephan : <https://doi.org/10.1007/s11214-017-0385-1>
- * Nighttime (FUV) O+ profiles: Dr. Farzad Kamalabadi : <https://doi.org/10.1007/s11214-018-0502-9>
- * Neutral Wind profiles: Dr. Jonathan Makela : <https://doi.org/10.1007/s11214-017-0359-3>
- * Neutral Temperature profiles: Dr. Christoph Englert : <https://doi.org/10.1007/s11214-017-0434-9>
- * Ion Velocity Measurements : Dr. Russell Stoneback : <https://doi.org/10.1007/s11214-017-0383-3>

Responsibility for Level 4 products falls to those scientists responsible for those products.

- * Hough Modes : Dr. Chihoko Yamashita : <https://doi.org/10.1007/s11214-017-0401-5>
- * TIEGCM : Dr. Astrid Maute : <https://doi.org/10.1007/s11214-017-0330-3>
- * SAMI3 : Dr. Joseph Huba : <https://doi.org/10.1007/s11214-017-0415-z>

Pre-production versions of all above papers are available on the ICON website.

<http://icon.ssl.berkeley.edu/Publications>

Overall validation of the products is overseen by the ICON Project Scientist, Dr. Scott England.

NASA oversight for all products is provided by the Mission Scientist, Dr. Jeffrey Klenzing.

Users of these data should contact and acknowledge the Principal Investigator Dr. Immel and the party directly responsible for the data product (noted above) and acknowledge NASA funding for the collection of the data used in the research with the following statement : "ICON is supported by NASA's Explorers Program through contracts NNG12FA45C and NNG12FA42I".

These data are openly available as described in the ICON Data Management Plan available on the ICON website (<http://icon.ssl.berkeley.edu/Data>).

This document was automatically generated on 2020-09-22 08:41 using the file:

ICON_L1_FUV_LWP_2020-09-13_v03r000.NC

Software version: ICON SDC > ICON FUV L1 Processor v1.0