# ICON Data Product 1.1,1.2: MIGHTI Calibrated LOS Winds and Temperature Array

This document describes the data product for ICON MIGHTI-B Level 1.1, 1.2 Calibrated Science Image File, which is in NetCDF4 format.

This file contains MIGHTI fringe information for wind retrieval and uncalibrated IR intensities (in electrons/s) for temperature retrieval.

The MIGHTI image is separated into three regions corresponding to the atmospheric emission collected: the red side (630.0 nm), the green side (557.7 nm), and the IR mosaic (760 - 765 nm).

For the wind retrieval the fringes are analyzed for envelope (fringe amplitude) and phase delta as compared to the previously determined phase of a fringe representing zero motion of the atmosphere.

Various instrument and spacecraft parameters are provided by or derived from information in an ancillary file which includes housekeeping data (thermal sensors, pointing data, etc) from the entire day.

ECEF stands for Earth Centered Earth Fixed and ECI for Earth Centered Inertial.

Further information on the instrument and analysis processes can be found in https://doi.org/10.1364/FTS.2015.FM4A.1 by C. Englert, et. al., OSA 2015.

## **History**

MIGHTI L1 Processing Code. Written by K. Marr, et al. Began 1/1/17.

Initial release: Version 1.3.0. Provides: Red and green line of sight fringe phases (less zero wind phase), red and green amplitudes, IR counts per second, red and green line of sight brightness profiles, tangent point geophysical data, and associated uncertainties. Processing includes: Spike correction, flatfield correction, fringe visibility correction, phase distortion correction, thermal effect correction, and image transfer pickup correction.

2nd release: Version 2.0.0. Includes sensor lateral shift calculation (notches) and correction. Update to zero wind determination.

### **Dimensions**

NetCDF files contain **variables** and the **dimensions** over which those variables are defined. First, the dimensions are defined, then all variables in the file are described.

The dimensions used by the variables in this file are given below, along with nominal sizes. Note that the size may vary from file to file. For example, the "Epoch" dimension, which describes the number of time samples contained in this file, will have a varying size.

Dimension Name	Nominal Size
Epoch	1
ICON_L1_MIGHTI_B_IR_Array_Pixel_Index	413
ICON_L1_MIGHTI_B_IR_Array_Altitudes	20
ICON_L1_MIGHTI_B_Green_Array_OPD	362

Dimension Name	Nominal Size
ICON_L1_MIGHTI_B_Red_Array_OPD	323
ICON_L1_MIGHTI_B_Green_Array_Altitudes	82
ICON_L1_MIGHTI_B_Red_Array_Altitudes	60
ICON_L1_MIGHTI_B_Vector_LLA	3
ICON_L1_MIGHTI_B_Vector_XYZ	3
ICON_L1_MIGHTI_B_Vector_Roll	3
ICON_L1_MIGHTI_B_Time_Channel	3
ICON_L1_MIGHTI_B_IR_Channel	5
ICON_LO_MIGHTI_B_Image_ROI_Columns	92
ICON_LO_MIGHTI_B_Image_ROI_Rows	929

## **Variables**

Variables in this file are listed below. First, "data" variables are described, followed by the "support\_data" variables, and finally the "metadata" variables. The variables classified as "ignore\_data" are not shown.

#### data

Variable Name	Description	Units	Dimensions
ICON_L1_MIGHTI_B_IR _Array	CCD response per second to incident photons corresponding to the five IR filters  CCD response per second to incident photons corresponding to the five IR filters by OPD and altitude.  Raw CCD counts have been gain normalized and divided by integration time.	Rel. R ( Electro ns/s)	Epoch, ICON_L1_ MIGHTI_B_IR_Arr ay_Altitudes, I CON_L1_MIGHTI_B _IR_Array_Pixel _Index
ICON_L1_MIGHTI_B_IR _Array_Tangent_LatL onAlt	Tangent point latitudes, longitudes, and altitudes for IR altitudes - middle of FoV, all altitudes  Tangent point latitudes, longitudes, and altitudes for IR side.  Taken at middle of FoV for all altitudes at start, middle, and end of integration.	degree s, degr ees, km	Epoch, ICON_L1_ MIGHTI_B_Time_C hannel, ICON_L1 _MIGHTI_B_Vecto r_LLA, ICON_L1_ MIGHTI_B_IR_Arr ay_Altitudes
ICON_L1_MIGHTI_B_IR _Array_Tangent_Loca l_Solar_Time	Tangent point local solar time for IR altitudes at middle of FoV  Tangent point local solar times for IR array.  Taken at middle of FoV for all altitudes at start, middle, and end of integration.	hr	Epoch, ICON_L1_ MIGHTI_B_Time_C hannel, ICON_L1 _MIGHTI_B_IR_Ar ray_Altitudes
ICON_L1_MIGHTI_B_IR _Array_Tangent_Azim uth_Angle	Tangent point azimuth angle for IR altitudes at middle of FoV  Azimuth angle (between line of sight and local north) at tangent points for IR array.  Taken at middle of FoV for all altitudes at start, middle, and end of integration.  Line of sight is the vector pointing from the spacecraft to the tangent point. At the tangent point, this vector is parallel to the ground. This variable follows the typical geophysical convention of degrees East of North (North=0, East=90, South=180, West=270). It can vary by a few degrees from the top of the profile to the bottom, so one value is reported per altitude. MIGHTI-A and MIGHTI-B will have values approximately 90 degrees apart.	degree s	Epoch, ICON_L1_ MIGHTI_B_Time_C hannel, ICON_L1 _MIGHTI_B_IR_Ar ray_Altitudes
ICON_L1_MIGHTI_B_IR _Array_Tangent_Sola r_Zenith_Angle	Tangent point solar zenith angle for IR altitudes at middle of FoV  Tangent point solar zenith angle for IR array.  Taken at middle of FoV for all altitudes at start, middle, and end of integration.	degree s	Epoch, ICON_L1_ MIGHTI_B_Time_C hannel, ICON_L1 _MIGHTI_B_IR_Ar ray_Altitudes

Variable Name	Description	Units	Dimensions
ICON_L1_MIGHTI_B_IR _Array_Tangent_Magn etic_Latitude	Tangent point magnetic latitude  Tangent point magnetic latitude for IR array.  Taken at middle of FoV for all altitudes at start, middle, and end of integration.  Quasi-dipole latitude and longitude are calculated using the fast implementation developed by Emmert et al. (2010, doi:10.1029/2010JA015326) and the Python wrapper apexpy (doi.org/10.5281/zenodo.1214207).  Quasi-dipole longitude is defined such that zero occurs where the geodetic longitude is near 285 deg east (depending on latitude).	degree s	Epoch, ICON_L1_ MIGHTI_B_Time_C hannel, ICON_L1 _MIGHTI_B_IR_Ar ray_Altitudes
ICON_L1_MIGHTI_B_IR _Array_Tangent_Magn etic_Longitude	Tangent point magnetic longitude  Tangent point magnetic longitude for IR array.  Taken at middle of FoV for all altitudes at start, middle, and end of integration.  Quasi-dipole latitude and longitude are calculated using the fast implementation developed by Emmert et al. (2010, doi:10.1029/2010JA015326) and the Python wrapper apexpy (doi.org/10.5281/zenodo.1214207).  Quasi-dipole longitude is defined such that zero occurs where the geodetic longitude is near 285 deg east (depending on latitude).	degree s	Epoch, ICON_L1_ MIGHTI_B_Time_C hannel, ICON_L1 _MIGHTI_B_IR_Ar ray_Altitudes
ICON_L1_MIGHTI_B_SC _Altitude	Spacecraft Altitude Spacecraft altitude at start, middle, and end of integration.	km	Epoch, ICON_L1_ MIGHTI_B_Time_C hannel
ICON_L1_MIGHTI_B_SC _Latitude	Spacecraft latitude Spacecraft latitude at start, middle, and end of integration.	degree s	Epoch, ICON_L1_ MIGHTI_B_Time_C hannel
ICON_L1_MIGHTI_B_SC _Longitude	Spacecraft longitude Spacecraft longitude at start, middle, and end of integration.	degree s	Epoch, ICON_L1_ MIGHTI_B_Time_C hannel
ICON_L1_MIGHTI_B_To tal_Boresight_Sun_A ngle	Total angle between the MIGHTI boresight and the sun  Total (not component) angle between the MIGHTI boresight and the sun at start, middle, and end of integration.	degree s	Epoch, ICON_L1_ MIGHTI_B_Time_C hannel
ICON_L1_MIGHTI_B_Gr een_Phase	Phase difference between the green atmospheric line and the associated calibration line minus the corresponding Zero Wind delta - by optical path difference (OPD) and altitude  Phase difference between the green atmospheric line and the associated calibration line minus the corresponding Zero Wind delta - by optical path difference (OPD) and altitude.	rad	Epoch, ICON_L1_ MIGHTI_B_Green_ Array_Altitudes , ICON_L1_MIGHT I_B_Green_Array _OPD

Variable Name	Description	Units	Dimensions
ICON_L1_MIGHTI_B_Gr een_Envelope	Envelopes of the green atmospheric fringes by optical path difference (OPD) and altitude  Envelopes (fringe amplitudes) of the green atmospheric interferograms by optical path difference (OPD) and altitude.	Rel R	Epoch, ICON_L1_ MIGHTI_B_Green_ Array_Altitudes , ICON_L1_MIGHT I_B_Green_Array _OPD
ICON_L1_MIGHTI_B_Gr een_Relative_Bright ness	Relative brightness of green emission by altitude  Relative brightness of green emission by altitude.  Average of signal + DC for each altitude.  SDL calibration used to convert counts to brightness.	Rayleig hs	Epoch, ICON_L1_ MIGHTI_B_Green_ Array_Altitudes
ICON_L1_MIGHTI_B_Gr een_Phase_Uncertain ties	Uncertainties of the phases of the green atmospheric line by altitude  Uncertainties of the phase deltas of the green atmospheric line by altitude.  Calculated from total signal, modulated signal, and first principles based on assumption of shot noise dominance.	rad	Epoch, ICON_L1_ MIGHTI_B_Green_ Array_Altitudes
ICON_L1_MIGHTI_B_Gr een_Envelope_Uncert ainties	Uncertainties of the envelopes of the green atmospheric fringes by altitude  Uncertainties of the envelopes of the green atmospheric fringes by altitude.  Calculated from total signal, modulated signal, and first principles based on assumption of shot noise dominance.	Rel R	Epoch, ICON_L1_ MIGHTI_B_Green_ Array_Altitudes
ICON_L1_MIGHTI_B_Gr een_Tangent_LatLonA lt	Tangent point latitudes, longitudes, and altitudes for green side - middle of FoV, all altitudes  Tangent point latitudes, longitudes, and altitudes for green side.  Taken at middle of FoV for all altitudes at start, middle, and end of integration.	degree s, degr ees, km	Epoch, ICON_L1_ MIGHTI_B_Time_C hannel, ICON_L1 _MIGHTI_B_Vecto r_LLA, ICON_L1_ MIGHTI_B_Green_ Array_Altitudes
ICON_L1_MIGHTI_B_Gr een_Tangent_Local_S olar_Time	Tangent point local solar time for green side altitudes at middle of FoV  Tangent point local solar times for green side.  Taken at middle of FoV for all altitudes at start, middle, and end of integration.	hr	Epoch, ICON_L1_ MIGHTI_B_Time_C hannel, ICON_L1 _MIGHTI_B_Green _Array_Altitude s

Variable Name	Description	Units	Dimensions
ICON_L1_MIGHTI_B_Gr een_Tangent_Magneti c_Latitude	Tangent point magnetic latitudes for green side altitudes at middle of FoV	degree s	Epoch, ICON_L1_ MIGHTI_B_Time_C hannel, ICON_L1
C_Latitude	Tangent point magnetic latitudes for green side.		_MIGHTI_B_Green
	Taken at middle of FoV for all altitudes at start, middle, and end of integration.		_Array_Altitude
	Quasi-dipole latitude and longitude are calculated using the fast implementation developed by Emmert et al. (2010, doi:10.1029/2010JA015326) and the Python wrapper apexpy (doi.org/10.5281/zenodo.1214207).		
	Quasi-dipole longitude is defined such that zero occurs where the geodetic longitude is near 285 deg east (depending on latitude).		
ICON_L1_MIGHTI_B_Gr een_Tangent_Magneti c_Longitude	Tangent point magnetic longitudes for green side altitudes at middle of FoV	degree s	Epoch, ICON_L1_ MIGHTI_B_Time_C hannel, ICON_L1
c_hongredac	Tangent point magnetic longitudes for green side.		_MIGHTI_B_Green
	Taken at middle of FoV for all altitudes at start, middle, and end of integration.		_Array_Altitude
	Quasi-dipole latitude and longitude are calculated using the fast implementation developed by Emmert et al. (2010, doi:10.1029/2010JA015326) and the Python wrapper apexpy (doi.org/10.5281/zenodo.1214207).		
	Quasi-dipole longitude is defined such that zero occurs where the geodetic longitude is near 285 deg east (depending on latitude).		
ICON_L1_MIGHTI_B_Gr een_Tangent_Solar_Z	Tangent point solar zenith angle for green side altitudes at middle of FoV	degree s	Epoch, ICON_L1_ MIGHTI_B_Time_C
enith_Angle	Tangent point solar zenith angles for green side.		hannel, ICON_L1 _MIGHTI_B_Green
	Taken at middle of FoV for all altitudes at start, middle, and end of integration.		_Array_Altitude
ICON_L1_MIGHTI_B_Re d_Phase	Phase difference between the red atmospheric line and the associated calibration line minus the corresponding Zero Wind delta - by optical path difference (OPD) and altitude  Phase difference between the red atmospheric line and the	rad	Epoch, ICON_L1_ MIGHTI_B_Red_Ar ray_Altitudes, ICON_L1_MIGHTI_ B_Red_Array_OPD
	associated calibration line minus the corresponding Zero Wind delta - by optical path difference (OPD) and altitude.		
ICON_L1_MIGHTI_B_Re d_Envelope	Envelopes of the red atmospheric fringes by optical path differnce (OPD) and altitude	Rel R	Epoch, ICON_L1_ MIGHTI_B_Red_Ar ray_Altitudes,
	Envelopes (fringe amplitudes) of the red atmospheric interferograms by optical path difference (OPD) and altitude.		ICON_L1_MIGHTI_ B_Red_Array_OPD

Variable Name	Description	Units	Dimensions
ICON_L1_MIGHTI_B_Re d_Relative_Brightne ss	Relative brightness of the red emission by altitude  Relative brightness of the red emission by altitude.  Average of signal + DC for each altitude.  SDL calibration used to convert counts to brightness.	Rayleig hs	Epoch, ICON_L1_ MIGHTI_B_Red_Ar ray_Altitudes
ICON_L1_MIGHTI_B_Re d_Phase_Uncertainti es	Uncertainties of the phase deltas of the red atmospheric line by altitude  Uncertainties of the phase deltas of the red atmospheric line by altitude.  Calculated from total signal, modulated signal, first principles based on assumption of shot noise dominance.	rad	Epoch, ICON_L1_ MIGHTI_B_Red_Ar ray_Altitudes
ICON_L1_MIGHTI_B_Re d_Envelope_Uncertai nties	Uncertainties of the envelopes of the red atmospheric fringes by altitude  Uncertainties of the envelopes of the red atmospheric fringes by altitude.  Calculated from total signal, modulated signal, and first principles based on assumption of shot noise dominance.	Relativ e R	Epoch, ICON_L1_ MIGHTI_B_Red_Ar ray_Altitudes
ICON_L1_MIGHTI_B_Re d_Tangent_LatLonAlt	Tangent point latitudes, longitudes, and altitudes for red side - middle of FoV, all altitudes  Tangent point latitudes, longitudes, and altitudes for red side.  Taken at middle of FoV for all altitudes at start, middle, and end of integration.	degree s, degr ees, km	Epoch, ICON_L1_ MIGHTI_B_Time_C hannel, ICON_L1 _MIGHTI_B_Vecto r_LLA, ICON_L1_ MIGHTI_B_Red_Ar ray_Altitudes
ICON_L1_MIGHTI_B_Re d_Tangent_Local_Sol ar_Time	Tangent point local solar time for red side altitudes at middle of FoV  Tangent point local solar times for red side.  Taken at middle of FoV for all altitudes at start, middle, and end of integration.	hr	Epoch, ICON_L1_ MIGHTI_B_Time_C hannel, ICON_L1 _MIGHTI_B_Red_A rray_Altitudes
ICON_L1_MIGHTI_B_Re d_Tangent_Magnetic_ Latitude	Tangent point magnetic latitudes for red side altitudes at middle of FoV  Tangent point magnetic latitudes for red side.  Taken at middle of FoV for all altitudes at start, middle, and end of integration.  Quasi-dipole latitude and longitude are calculated using the fast implementation developed by Emmert et al. (2010, doi:10.1029/2010JA015326) and the Python wrapper apexpy (doi.org/10.5281/zenodo.1214207).  Quasi-dipole longitude is defined such that zero occurs where the geodetic longitude is near 285 deg east (depending on latitude).	degree s	Epoch, ICON_L1_ MIGHTI_B_Time_C hannel, ICON_L1 _MIGHTI_B_Red_A rray_Altitudes

Variable Name	Description	Units	Dimensions
ICON_L1_MIGHTI_B_Re d_Tangent_Magnetic_ Longitude	Tangent point magnetic longitudes for red side altitudes at middle of FoV	degree s	Epoch, ICON_L1_ MIGHTI_B_Time_C hannel, ICON_L1
Doligicade	Tangent point magnetic longitudes for red side.		_MIGHTI_B_Red_A
	Taken at middle of FoV for all altitudes at start, middle, and end of integration.		rray_Altitudes
	Quasi-dipole latitude and longitude are calculated using the fast implementation developed by Emmert et al. (2010, doi:10.1029/2010JA015326) and the Python wrapper apexpy (doi.org/10.5281/zenodo.1214207).		
	Quasi-dipole longitude is defined such that zero occurs where the geodetic longitude is near 285 deg east (depending on latitude).		
ICON_L1_MIGHTI_B_Re d_Tangent_Solar_Zen	Tangent point solar zenith angle for red side altitudes at middle of FoV	degree s	Epoch, ICON_L1_ MIGHTI_B_Time_C
ith_Angle	Tangent point solar zenith angles for red side.		hannel, ICON_L1 _MIGHTI_B_Red_A
	Taken at middle of FoV for all altitudes at start, middle, and end of integration.		rray_Altitudes
ICON_L1_MIGHTI_B_Gr een_ECEF_Unit_Vecto rs	ECEF Unit Vectors per pixel representing the green lines of sight		Epoch, ICON_L1_ MIGHTI_B_Vector _XYZ, ICON_L1_M
	ECEF Unit Vectors per pixel representing the green lines of sight.		IGHTI_B_Green_A rray_Altitudes,
	Calculated from the boresight ECEF vector and pixel-to-view-angle ground calibrations, as documented in the MIGHTI alignment report.		ICON_L1_MIGHTI_ B_Green_Array_O PD
	By OPD and altitude at start, middle and end of the integration.		
ICON_L1_MIGHTI_B_Re d_ECEF_Unit_Vectors	ECEF Unit Vectors per pixel representing the red lines of sight		Epoch, ICON_L1_ MIGHTI_B_Vector
	ECEF Unit Vectors per pixel representing the red lines of sight.		_XYZ, ICON_L1_M IGHTI_B_Red_Arr
	Calculated from the boresight ECEF vector and pixel-to-view-angle ground calibrations, as documented in the alignment report.		ay_Altitudes, I CON_L1_MIGHTI_B _Red_Array_OPD
	By OPD and altitude at start, middle and end of the integration.		
ICON_LO_MIGHTI_B_Im age_ROI_Pixels	MIGHTI region of interest pixel values layed out [ROWS]x[COLUMNS].	Count	Epoch, ICON_LO_ MIGHTI_B_Image_
	The entire unrotated imaged region from MIGHTI. Typically 92 x 929 pixels (altitude x optical path difference). During processing this image is rotated ninety degrees clockwise and then split into red, green, and IR regions.		ROI_Rows, ICON_ LO_MIGHTI_B_Ima ge_ROI_Columns

Variable Name	Description	Units	Dimensions
Epoch	Milliseconds since 1970-01-01 00:00:00 UTC at middle of image integration	ms	Epoch
	Milliseconds since 1970-01-01 00:00:00 UTC at middle of image integration.		
ICON_L1_MIGHTI_B_IR	Pixel indices corresponding to the IR filter mosaic		Epoch, ICON_L1_
_Array_Pixel_Index	Pixel (OPD) indices corresponding to the IR filter mosaic (1st dimension).		MIGHTI_B_IR_Arr ay_Pixel_Index
ICON_L1_MIGHTI_B_IR	Tangent altitudes corresponding to the five IR filters	km	Epoch, ICON_L1_
_Array_Altitudes	Tangent altitudes corresponding to the rows of the IR filter mosaic (2nd dimension).		MIGHTI_B_IR_Arr ay_Altitudes
ICON_L1_MIGHTI_B_Gr	Data quality Factor by altitude for 557nm		Epoch, ICON_L1_
een_Quality_Factor	Data quality Factor by altitude for green line.		MIGHTI_B_Green_ Array_Altitudes
	0: unable to analyze data		
	0.5: data has one or more of the issues listed below		
	1.0: good data		
	Reasons for 0.5 setting: Thermal Drift calibration file greater than 3 days old, uncertainty in green phases greater than 0.35.		
ICON_L1_MIGHTI_B_Gr een_Array_OPD	Optical path differences corresponding to the L1 green side pixels (along fringe pattern)	cm	Epoch, ICON_L1_ MIGHTI_B_Green_
	Optical path differences corresponding to the L1 green side pixels (along fringe pattern).		Array_OPD
	The OPD increases from left to right in L1 rotated coordinates and is used to convert phase deltas to atmospheric winds as demonstrated in https://doi.org/10.1364/FTS.2015.FM4A.1 by C. Englert, et. al., OSA 2015.		
	OPD range is roughly 4.9 - 5.9 cm depending on region of interest.		
ICON_L1_MIGHTI_B_Gr een_Array_Altitudes	Tangent altitudes corresponding to the green fringes - middle of integration, middle of FoV	km	Epoch, ICON_L1_ MIGHTI_B_Green_
	Tangent altitudes corresponding to the rows of the green fringes.		Array_Altitudes
	Taken from middle of integration time at middle of FoV.		
ICON_L1_MIGHTI_B_Re d_Quality_Factor	Data quality Factor by altitude for 630nm		Epoch, ICON_L1_
	Data quality Factor by altitude for red line.		MIGHTI_B_Red_Ar ray_Altitudes
	0.0: unable to analyze data		
	0.5: data has one or more of the issues listed below		
	1.0: good data		
	Reasons for 0.5 setting: Thermal Drift calibration file greater than 3 days old, uncertainty in red phases greater than 0.35.		

Variable Name	Description	Units	Dimensions
ICON_L1_MIGHTI_B_Re d_Array_OPD	Optical path differences corresponding to the L1 red side pixels (along fringe pattern)	cm	Epoch, ICON_L1_ MIGHTI_B_Red_Ar ray_OPD
	Optical path differences corresponding to the L1 red side pixels (along fringe pattern).		
	The OPD increases from left to right in L1 rotated coordinates and is used to convert phase deltas to atmospheric winds as demonstrated in https://doi.org/10.1364/FTS.2015.FM4A.1 by C. Englert, et. al., OSA 2015.		
	OPD range is roughly 4.9 - 5.9 cm depending on region of interest.		
ICON_L1_MIGHTI_B_Re d_Array_Altitudes	Tangent altitudes corresponding to the red fringes - middle of integration, middle of FoV	km	Epoch, ICON_L1_ MIGHTI_B_Red_Ar ray_Altitudes
	Tangent altitudes corresponding to the rows for the red fringes		1-
	Taken from middle of integration time at middle of FoV.		
ICON_L1_MIGHTI_B_SC _Position_ECEF	Spacecraft Position Vector in ECEF	km	Epoch, ICON_L1_ MIGHTI_B_Time_C
	Spacecraft Position Vector in ECEF as given in the MIGHTI ancillary file.		hannel, ICON_L1 _MIGHTI_B_Vecto r_XYZ
ICON_L1_MIGHTI_B_SC _Velocity_ECEF	ECEF Vector for spacecraft velocity	m/s	Epoch, ICON_L1_ MIGHTI_B_Time_C
	ECEF Vector for spacecraft velocity as given in the MIGHTI ancillary file.		hannel, ICON_L1 _MIGHTI_B_Vecto r_XYZ
ICON_L1_MIGHTI_B_Im age_Times	Epochs corresponding to the Start, Middle, and Stop of the integration	ms	Epoch, ICON_L1_ MIGHTI_B_Time_C hannel
	Epochs corresponding to the start, middle, and end of the integration.		THAT THE T
ICON_L1_MIGHTI_B_Ro l1_Angles	Roll angles of the field of view	degree s, degr	Epoch, ICON_L1_ MIGHTI_B_Vector
	Roll angles of the field of view.	ees, de	_Roll
	Order: Boresight angle, CCD_Limb angle, CCD_Altitudes angle.	grees	
ICON_L1_MIGHTI_B_Qu ality_Flag_Low_Sign al_To_Noise_Red	Quality Flag indicating low signal to noise in red signal		Epoch, ICON_L1_ MIGHTI_B_Red_Ar
	Quality Flag indicating low signal to noise for red signal by altitude. Half up means the uncertainty is above 0.35rad. Full up means single-row analysis was impossible.		ray_Altitudes
ICON_L1_MIGHTI_B_Qu ality_Flag_Low_Sign	Quality Flag indicating low signal to noise in green signal		Epoch, ICON_L1_ MIGHTI_B_Green_
al_To_Noise_Green	Quality Flag indicating low signal to noise for green signal by altitude. Half up means the uncertainty is above 0.35rad. Full up means single-row analysis was impossible.		Array_Altitudes

Variable Name	Description	Units	Dimensions
ICON_L1_MIGHTI_B_Qu ality_Flag_SAA	Quality Flag indicating that the spacecraft is within the South Atlantic Anomaly		Epoch
	Quality Flag indicating that the spacecraft is within the South Atlantic Anomaly based on the spacecraft status register.		
ICON_L1_MIGHTI_B_Qu ality_Flag_Bad_Cali bration	Quality Flag indicating an inappropriate calibration file has been used or was missing		Epoch
bration	Quality Flag indicating a thermal drift file older than three days has been used.		
ICON_L1_MIGHTI_B_Qu ality_Flag_Sun_Moon	Quality Flag indicating that either the Sun or Moon is in or near the field of view.		Epoch
_in_FoV	Quality Flag indicating either the Sun or Moon is in or near the field of view.		
	Half up means the moon was within 5 degrees of the field of view for this image.		
	Full up means the Sun is within 7 degrees of the field of view at some point during the day.		
	For both cases the quality factors are set to zero for the whole image.		
ICON_L1_MIGHTI_B_SC	Spacecraft Attitude Control Register		Epoch
_Attitude_Control_R egister	Spacecraft Attitude Control Register.		
	Bit 0: LVLH NORMAL		
	Bit 1: LVLH Reverse Mode		
	Bit 2: Earth Limb Pointing		
	Bit 3: Inertial Pointing		
	Bit 4: Stellar Pointing		
	Bit 5: Attitude Slew		
	Bit 6: Conjugate Maneuver		
	Bit 7: Nadir Calibration		
	Bit 8: Lunar Calibration		
	Bit 9: Stellar Calibration		
ICON_L1_MIGHTI_B_SC _Pointing_Jitter	Spacecraft Pointing Jitter	degree s	Epoch
_FOINCING_UITTE	Spacecraft pointing jitter.		
	On the basis of the ECEF quaternion ephemeris, a 60-second window is found.		
	Over that window a linear fit is found.		
	A residual between the actual values and linear fit is calculated.		
	The standard deviation of that residual is reported as the jitter.		
	The closest ehemeris time to the MIGHTI middle time is used in this variable.		

Variable Name	Description	Units	Dimensions
ICON_LO_MIGHTI_B_Ti me_UTC	ISO 9601 formatted UTC timestamp (at middle of image integration).		Epoch
	ISO 9601 formatted UTC timestamp (at middle of image integration).		
	Derived from original GPS values reported from spacecraft (Time_GPS_Seconds and Time_GPS_Subseconds).		
	Time calculation is offset by 615ms (flush time) for the first image in the series and for all other images are adjusted by subtracting (integration time + 308 milliseconds) from the reported GPS time then adding the difference between the readout FRT and the header FRT.		
	Time may be delayed by up to 10 ms due to FSW polling delay.		
	Minimum allowed value for this variable is 1970-01-01 00:00:00 UTC and maximum allowed value is 2150-01-01 00:00:00 UTC.		
	All character arrays are NULL terminated (size includes NULL).		
ICON_LO_MIGHTI_B_Ti me_GPS	Milliseconds since 1980-01-06 00:00:00 TAI (coincident with UTC) at middle of image integration.	millisec onds	Epoch
	Milliseconds since 1980-01-06 00:00:00 TAI (coincident with UTC) at middle of image integration.		
	Derived from original GPS values reported from spacecraft (Time_GPS_Seconds and Time_GPS_Subseconds).		
	Time calculation is offset by 615ms (flush time) for the first image in the series and for all other images are adjusted by subtracting (integration time + 308 milliseconds) from the reported GPS time then adding the difference between the readout FRT and the header FRT.		
	Time may be delayed by up to 10 ms due to FSW polling delay.		
	Minimum allowed value for this variable is a long integer corresponding to 1980-01-06 00:00:00 UTC and maximum allowed value is a long integer corresponding to a time in year 2154 UTC.		

Variable Name	Description	Units	Dimensions
ICON_LO_MIGHTI_B_Ti me_UTC_Start	Milliseconds since 1970-01-01 00:00:00 UTC at start of image integration.	millisec onds	Epoch
	Milliseconds since 1970-01-01 00:00:00 UTC at start of image integration.		
	Derived from original GPS values reported from spacecraft (Time_GPS_Seconds and Time_GPS_Subseconds).		
	Time calculation is offset by 615ms (flush time) for the first image in the series and for all other images are adjusted by subtracting (integration time + 308 milliseconds) from the reported GPS time then adding the difference between the readout FRT and the header FRT.		
	Time may be delayed by up to 10 ms due to FSW polling delay.		
	Minimum allowed value for this variable is a long integer corresponding to 1970-01-01 00:00:00 UTC and maximum allowed value is a long integer corresponding to a time in year 2160 UTC.		
ICON_LO_MIGHTI_B_Ti me_UTC_Stop	Milliseconds since 1970-01-01 00:00:00 UTC at end of image integration.	millisec onds	Epoch
	Milliseconds since 1970-01-01 00:00:00 UTC at end of image integration.		
	Derived from original GPS values reported from spacecraft (Time_GPS_Seconds and Time_GPS_Subseconds).		
	Time calculation is offset by 615ms (flush time) for the first image in the series and for all other images are adjusted by subtracting (integration time + 308 milliseconds) from the reported GPS time then adding the difference between the readout FRT and the header FRT.		
	Time may be delayed by up to 10 ms due to FSW polling delay.		
	Minimum allowed value for this variable is a long integer corresponding to 1970-01-01 00:00:00 UTC and maximum allowed value is a long integer corresponding to a time in year 2160 UTC.		
ICON_LO_MIGHTI_B_Ti me_GPS_Seconds	GPS seconds count when FSW received image packet header.	Second s	Epoch
	GPS seconds count when FSW received image packet header.		
	The FSW received the header of the first image in a series		
	615ms after start of image processing. Following headers are adjusted by subtracting (integration time + 308 milliseconds) from the reported GPS time then adding the difference between the readout FRT and the header FRT.		
	Time may be delayed by up to 10 ms due to FSW polling delay.		

Variable Name	Description	Units	Dimensions
ICON_LO_MIGHTI_B_Ti me_GPS_Subseconds	FSW 20MHz clock (50 nanosecond) offset from GPS seconds.  FSW 20MHz clock (50 nanosecond) offset from GPS seconds.	50 Nan osecon ds	Epoch
	The FSW received the header of the first image in a series 615ms after start of image processing. Following headers are adjusted by subtracting (integration time + 308 milliseconds) from the reported GPS time then adding the difference between the readout FRT and the header FRT.		
	The offset may be more than 1 second but never 2 or more seconds.		
	Time may be delayed by up to 10 ms due to FSW polling delay.		
ICON_LO_MIGHTI_B_Ti me_Integration	Time to integrate MIGHTI-B region of interest (ROI) image.	millisec onds	Epoch
ICON_LO_MIGHTI_B_Ti me_Header_Free_Runn ing_Timer	Free running timer reading for MIGHTI image header.  The FRTs are millisecond free running timers used to calculate the time offset for this image's integration from the observatory GPS time tag. This is only used when it is not the first image in the integration sequence. When the prior image FRT is not known a timing error is generated as a calculation cannot be performed. The base GPS time is used as the start time.	millisec onds	Epoch
ICON_LO_MIGHTI_B_Ti me_Readout_Free_Run ning_Timer	Free running timer reading for MIGHTI image data readout start.  The FRTs are millisecond free running timers used to calculate the time offset for this image's integration from the observatory GPS time tag. This is only used when it is not the first image in the integration sequence. When the prior image FRT is not known a timing error is generated as a calculation cannot be performed. The base GPS time is used as the start time.	millisec onds	Epoch
ICON_LO_MIGHTI_B_Ti me_Prior_Readout_Fr ee_Running_Timer	Free running timer reading for MIGHTI prior image data readout start.  The FRTs are millisecond free running timers used to calculate the time offset for this image's integration from the observatory GPS time tag. This is only used when it is not the first image in the integration sequence. When the prior image FRT is not known a timing error is generated as a calculation cannot be performed. The base GPS time is used as the start time.	millisec onds	Epoch
ICON_LO_MIGHTI_B_Ti me_Prior_Known	Flag indicating prior image's free running timer known.  The FRTs are millisecond free running timers used to calculate the time offset for this image's integration from the observatory GPS time tag. This is only used when it is not the first image in the integration sequence. When the prior image FRT is not known a timing error is generated as a calculation cannot be performed. The base GPS time is used as the start time.	Flag	Epoch

Variable Name	Description	Units	Dimensions
ICON_LO_MIGHTI_B_MT _Device_ID	MIGHTI camera instrument ID (0=MIGHTI-A, 1=MIGHT-B).	Flag	
ICON_LO_MIGHTI_B_MT _Device_Current_Sen se	MIGHTI camera current (power) monitor count.	Count	Epoch
ICON_LO_MIGHTI_B_Ca libration_Lamp_1	MIGHTI camera calibration lamp 1 setting (0=OFF, 1=ON).	Flag	Epoch
	MIGHTI krypton (557.03 nm) camera calibration lamp 1 setting (0=OFF, 1=ON).		
ICON_L0_MIGHTI_B_Ca libration_Lamp_2	MIGHTI camera calibration lamp 2 setting (0=OFF, 1=ON).	Flag	Epoch
	MIGHTI neon (630.48 nm) camera calibration lamp 1 setting (0=OFF, 1=ON).		
ICON_L0_MIGHTI_B_Ca libration_Lamp_Curr ent	MIGHTI camera calibration lamp combined current monitor sense count.	Count	Epoch
ICON_L0_MIGHTI_B_Ca libration_Lamp_Temp erature	MIGHTI camera calibration lamp combined temperature monitor sense count.	Count	Epoch
ICON_L0_MIGHTI_B_In terferometer_1_Temp erature_Sense	MIGHTI interferometer 1 fine temperature sense count.	Count	Epoch
ICON_L0_MIGHTI_B_In terferometer_2_Temp erature_Sense	MIGHTI interferometer 2 fine temperature sense count.	Count	Epoch
ICON_LO_MIGHTI_B_Op tics_Bench_Temperat ure_Forward	MIGHTI optics bench forward temperature sense count.	Count	Epoch
ICON_LO_MIGHTI_B_Op tics_Bench_Temperat ure_Rear	MIGHTI optics bench rear temperature sense count.	Count	Epoch
ICON_LO_MIGHTI_B_Op tics_Temperature_Af t	MIGHTI optics aft temperature sense count.	Count	Epoch
ICON_LO_MIGHTI_B_TE C_Current_Input_Cou nt	MIGHTI thermo-electric cooler combined (TEC-A + TEC-B) input current count.	Count	Epoch
ICON_LO_MIGHTI_B_TE C_Temperature_Cold_ Count	MIGHTI thermo-electric cooler cold-side temperature sense count.	Count	Epoch
ICON_LO_MIGHTI_B_TE C_Temperature_Hot_C ount	MIGHTI thermo-electric cooler hot-side temperature sense count.	Count	Epoch

Variable Name	Description	Units	Dimensions
ICON_LO_MIGHTI_B_MT A_Aperturel_Positio	MIGHTI-A camera aperture 1 position sense flag.	Flag	Epoch
n	0=OPEN, 1=CLOSED, 2=15% OPEN, 3=UNKNOWN	FI	
ICON_LO_MIGHTI_B_MT A_Aperture2_Positio n	MIGHTI-A camera aperture 2 position sense flag.  0=OPEN, 1=CLOSED, 2=15% OPEN, 3=UNKNOWN	Flag	Epoch
ICON_LO_MIGHTI_B_MT A_Aperture1	MIGHTI-A camera aperture 1 switch setting (0=OPEN, 1=CLOSED).	Flag	Epoch
ICON_LO_MIGHTI_B_MT A_Aperture2	MIGHTI-A camera aperture 2 switch setting (0=OPEN, 1=CLOSED).	Flag	Epoch
ICON_LO_MIGHTI_B_MT B_Aperturel_Positio	MIGHTI-B camera aperture 1 position sense flag.	Flag	Epoch
n	0=OPEN, 1=CLOSED, 2=15% OPEN, 3=UNKNOWN		_
ICON_LO_MIGHTI_B_MT B_Aperture2_Positio n	MIGHTI-B camera aperture 2 position sense flag.  0=OPEN, 1=CLOSED, 2=15% OPEN, 3=UNKNOWN	Flag	Epoch
ICON_LO_MIGHTI_B_MT B_Aperture1	MIGHTI-B camera aperture 1 switch setting (0=OPEN, 1=CLOSED).	Flag	Epoch
ICON_L0_MIGHTI_B_MT B_Aperture2	MIGHTI-B camera aperture 2 switch setting (0=OPEN, 1=CLOSED).	Flag	Epoch
ICON_LO_MIGHTI_B_Er ror_Compression	Error count during compression (per packet).	Count	Epoch
	Error count during compression (per packet).		
	Should be zero (for no error) but if it is a non-zero number then the number indicates the number of packets that contained an overflow in the delta bit field during compression.		
ICON_LO_MIGHTI_B_Er ror_Time	Error finding prior image readout FRT (0=GOOD, 1=ERROR).	Flag	Epoch
	Error finding prior image readout FRT (0=GOOD, 1=ERROR).		
	The prior image read out FRT was missing so proper time offset couldn't be calculated correctly. The time will indicate later then the actual time. This only occurs when not the first image of the series.		
ICON_L0_MIGHTI_B_CC D_CS_Register	CCD CS register value from image header at end of integration.	Flag	Epoch
	CCD CS register value from image header at end of integration.		
	See ICN-ICD-002 (MIGHTI) for more details on this parameter.		

Variable Name	Description	Units	Dimensions
ICON_L0_MIGHTI_B_Ho rizontal_Charge_Tra nsfer_Efficiency_Co unt	Horizontal charge transfer efficiency register count indicating the horizontal overscan pixel configuration per MIGHTI ICD.  Horizontal charge transfer efficiency register count indicating the horizontal overscan pixel configuration per MIGHTI ICD.	Count	Epoch
	See ICN-ICD-002 (MIGHTI) for more details on this parameter.		
ICON_LO_MIGHTI_B_Im age_BIN_Parameters	MIGHTI binning parameters (BINCOUNTS).  MIGHTI binning parameters (BINCOUNTS).  See ICN-ICD-002 (MIGHTI) for more details on this parameter.	Flag	Epoch
	Bitwise register. Typical binning is 16 x 2 in unrotated coordinates.		
ICON_L0_MIGHTI_B_Im age_First	First image in MIGHTI integration sequence (0=NOT FIRST, 1=FIRST).	Flag	Epoch
ICON_LO_MIGHTI_B_Im age_ROI_Column_Coun t	MIGHTI region of interest (ROI) pixel column count.	Count	Epoch
ICON_LO_MIGHTI_B_Im age_ROI_Column_Star t	MIGHTI region of interest (ROI) pixel starting column.	Count	Epoch
ICON_LO_MIGHTI_B_Im age_ROI_Row_Count	MIGHTI region of interest (ROI) pixel row count.	Count	Epoch
ICON_LO_MIGHTI_B_Im age_ROI_Row_Start	MIGHTI region of interest (ROI) pixel starting row.	Count	Epoch

## metadata

Variable Name	Description	Units	Dimensions
ICON_L1_MIGHTI_B_Ve ctor_LLA	Vector labels corresponding to the tangent latitude, longitude, and altitude		ICON_L1_MIGHTI_ B_Vector_LLA
	Vector labels corresponding to the tangent latitude, longitude, and altitude.		
ICON_L1_MIGHTI_B_Ve	Vector labels corresponding to the ECEF lines of sight		ICON_L1_MIGHTI_ B_Vector_XYZ
ctor_XYZ	Vector labels corresponding to the ECEF lines of sight.		B_vector_xiz
ICON_L1_MIGHTI_B_Ve ctor_Roll	Vector labels corresponding to the field of view roll angles		ICON_L1_MIGHTI_ B_Vector_Roll
	Vector labels corresponding to the field of view roll angles.		
ICON_L1_MIGHTI_B_Ti me Channel	Vector labels corresponding to the time channels		ICON_L1_MIGHTI_ B Time Channel
	Vector labels corresponding to the time channels.		_ =

#### Acknowledgement

This is a data product from the NASA Ionospheric Connection Explorer mission, an Explorer launched at 21:59:45 EDT on October 10, 2019, from Cape Canaveral AFB in the USA. Guidelines for the use of this product are described in the ICON Rules of the Road (http://icon.ssl.berkeley.edu/Data).

Responsibility for the mission science falls to the Principal Investigator, Dr. Thomas Immel at UC Berkeley: Immel, T.J., England, S.L., Mende, S.B. et al. Space Sci Rev (2018) 214: 13. https://doi.org/10.1007/s11214-017-0449-2

Responsibility for the validation of the L1 data products falls to the instrument lead investigators/scientists.

- \* EUV: Dr. Eric Korpela: https://doi.org/10.1007/s11214-017-0384-2
- \* FUV: Dr. Harald Frey: https://doi.org/10.1007/s11214-017-0386-0
- \* MIGHTI: Dr. Christoph Englert : https://doi.org/10.1007/s11214-017-0358-4, and https://doi.org/10.1007/s11214-017-0374-4
- \* IVM: Dr. Roderick Heelis: https://doi.org/10.1007/s11214-017-0383-3

Responsibility for the validation of the L2 data products falls to those scientists responsible for those products.

- \* Daytime O and N2 profiles: Dr. Andrew Stephan: https://doi.org/10.1007/s11214-018-0477-6
- \* Daytime (EUV) O+ profiles: Dr. Andrew Stephan: https://doi.org/10.1007/s11214-017-0385-1
- \* Nighttime (FUV) O+ profiles: Dr. Farzad Kamalabadi : https://doi.org/10.1007/s11214-018-0502-9
- \* Neutral Wind profiles: Dr. Jonathan Makela: https://doi.org/10.1007/s11214-017-0359-3
- \* Neutral Temperature profiles: Dr. Christoph Englert: https://doi.org/10.1007/s11214-017-0434-9
- \* Ion Velocity Measurements: Dr. Russell Stoneback: https://doi.org/10.1007/s11214-017-0383-3

Responsibility for Level 4 products falls to those scientists responsible for those products.

- \* Hough Modes: Dr. Chihoko Yamashita: https://doi.org/10.1007/s11214-017-0401-5
- \* TIEGCM: Dr. Astrid Maute: https://doi.org/10.1007/s11214-017-0330-3
- \* SAMI3 : Dr. Joseph Huba : https://doi.org/10.1007/s11214-017-0415-z

Pre-production versions of all above papers are available on the ICON website. http://icon.ssl.berkeley.edu/Publications

Overall validation of the products is overseen by the ICON Project Scientist, Dr. Scott England.

NASA oversight for all products is provided by the Mission Scientist, Dr. Jeffrey Klenzing.

Users of these data should contact and acknowledge the Principal Investigator Dr. Immel and the party directly responsible for the data product (noted above) and acknowledge NASA funding for the collection of the data used in the research with the following statement: "ICON is supported by NASA's Explorers Program through contracts NNG12FA45C and NNG12FA42I".

These data are openly available as described in the ICON Data Management Plan available on the ICON website (http://icon.ssl.berkeley.edu/Data).